科林电气
KE ELECTRIC

Shanghai Stock Exchange
(SSE) I.D.: 603050

DDSY1277

Single Phase Two Wire Prepayment Energy Meter

- ***Compliant with STS 2.0 protocol regulations***
- ***Compliant with DLMS/COSEM protocol***
- ***Able to record event occurrence time and event codes, capable of storing and reading historical event information***
- ***Supports remote firmware updates and supports shell setting for power overload threshold***
- ***Configurable with 4 time-of-use electricity prices, with the ability to change time-of-use prices based on dates***
- ***Equipped with a keyboard on the meter or can be used in conjunction with a CIU, serving as a prepaid electricity meter***

BS

Multiple Connection Types

IP54 Ingress Protection

Remote Connection
Remote Disconnection

RS485 RS485 Interface

PLC

RF

GPRS

DLMS-COSEM
Compliance

STS Compliance


Loading Profile


Event Logs





Product Model: DDSY1277

Dimensions(mm)









Product Model:	DDSY1277
Basic Features:	
Meter Type:	Single Phase, Active
Material/Housing Standard:	Polycarbonate Glass Fiber Reinforces/BS
Connection Type:	Single Phase Two Wire
Nominal Voltage:	220V, 230V, 240V (80%~120%) (Optional)
Nominal Current (Max):	5(60)A 5(80)A 5A (100A) (Optional)
Frequency	50/60Hz
Power Consumption	<2W/10VA
Accuracy:	Active: Class 1
Meter Constant:	1000imp/kWh (Adjustable according to customized requirements)
Environmental Features:	
Operating Temperature:	–25℃ to + 70 ℃
Limit Temperature:	–40℃ to + 70 ℃
Storage Temperature:	–40℃ to + 85 ℃
Relative Humidity:	Up to 95% non–condensing
IP Grade:	IP54
Communication Interface:	
Local Communication:	RS485/Optical
Communication Module	PLC/RF/GPRS
Communication Protocol:	DLMS/COSEM
Keyboard	Equipped with a keyboard on the meter, in conjunction with CIU (Optional)
Other Features:	
LCD:	8 digit with 5 digit OBIS code
Instant Measurement:	Measuring instant current, voltage and power factor
Tariffs:	4 tariffs, 8 daily tariffs, 8 weekly tariffs, 6 seasonal tariffs (Optional)
Load Profiles:	8 channels for registering the load profile with programmable sampling time.
Logging:	Each individual event can be recorded at least 20 times (Optional)
Anti-Tampering:	Fraud/Tampering detection and logging (Optional)
Remote Control:	Remote disconnect/Reconnect using relay
Remote Metering:	Remote on demand/Scheduled meter reading
Security:	Message/Access authentication & encryption
Power/Alarm Management:	Power quality/Load process and alarms/Events management
Battery Capacity	⩾1200mAh
Dimension	Meter:207mm(L)*132mm(W)*76.7mm(H) CIU:125mm(L)*78mm(W)*32mm(H)

SHIJIAZHUANG KELIN ELECTRIC CO., LTD.

HQ:Nanjiangbi, Hongqi Street, Luquan District, Shijiazhuang City, Hebei Province, P. R. China.
Tel: +86 311 89176007 Fax: +86 311 85231087
Web: www.kechina.com E-mail: info@kechina.com